



ECE approval: **E11** 55R - 01 4309 Class S

Drawbar eye: Ø76, not axially rotatable, according to VG 74059 respectively class L according to ECE-55-01 or identically constructed.

Angular displacement of drawbar eye min horizontally: ±90° vertically: ±45° axially: ±360° with a minimum torque of 100Nm

D-value: 158kN

Dc-value: 90kN

Static support load: 1000kg respectively 1300kg

V-value: 35kN 31,3kN

Surface treatment according to RINGFEDER factory standard RS8319.

Greasing and other special treatments according to RINGFEDER factory standard RS10853.

ECE Genehmigung: **E11** 55R - 01 4309 Klasse S

Zugöse: Ø76, axial nicht drehbar, nach VG 74059 bzw. Klasse L nach ECE-55-01 oder baugleich

Winkelausschläge der Zugöse min horizontal: ±90° vertikal: ±45° axial: ±360° bei einem Mindestdrehmoment von 100Nm

Zul. D-Wert: 158kN

Zul. Dc-Wert: 90kN

Zul. stat. Stützlast 1000kg oder 1300kg

Zul. V-Wert: 35kN 31,3kN

Oberflächenbehandlung gem. RINGFEDER-Werksnorm RS8319.

Schmierung und andere Behandlungen gemäß RINGFEDER-Werksnorm RS10853.

<b>RINGFEDER</b>		02.11.2016 RB 14991250 RB A0 1:1 02.11.2016 RB 14991250 info
<b>VBG GROUP</b> Hook coupling Anhängerkupplung type RÜwg K4D, ECE 55-01		02.11.2016 RB 14991250 RB A0 1:1 02.11.2016 RB 14991250 info