



EG-Typgenehmigung:
EC-type approval:

e11 00 - 6292

ECE-Typgenehmigung:
ECE-type approval:

E11 55R - 01 6292

Klasse gemäss Richtlinie 94/20 EG sowie ECE 55-01:
class according to directive 94/20 EC or ECE 55-01:

Selbsttätige, nicht genormte Bolzenkupplung der Klasse S
Automatic non standard drawbar coupling class S

zur Verbindung mit Zugösen:
suitable for connection with drawbar eyes:

Zugösen 40mm nach ISO 8755 sowie Zugösen DIN 74054
Drawbar eyes 40mm acc. to ISO 8755 or acc. to DIN 74054

Winkelausschläge der Zugöse:
angles of drawbar eye:

Horizontal : ±110°
Vertikal : ± 20°
Axial : 360° bei einem Mindestdrehmoment von 100Nm
360° if using a minimum tightening torque of 100Nm

D:	137 kN
Dc:	92 kN
V:	40 kN
S:	1000 kg

VBG GROUP		Modified Date	Modified by	PU-number	Issue
		17.04.2012	HBH	10803	a
3D-Model No.		Checked by	Engineer	Signed by	
14991072		JR	HBH		
GENERAL TOLERANCE	MATERIAL	Sheet Size	Scale	Projection	Drafting Date
A2		1:4			07.02.2007
Machined surfaces	Quality	Foreign Drawing No.			
Unmachined surfaces	Type	Description Name			
Surface texture	Blank	Automatic drawbar coupling			
Mass	Surface treatment	Selbsttätige Bolzenkupplung			
36,2 kg	EC/ED/KETL 18-25 µm	Type 4040/G150 Ausf.B			
Usable for	Stage	Drawing No.			
		PI 14991072-info			
This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.					Remark
					Id. No.