



Tighten the screws according to mounting instruction  
 6 Hexagon socket screws  
 M16x min.50, ISO 4762 8.8  
 Tightening torque each screw 210 Nm  
 Anzugsverfahren siehe Einbauanweisung  
 6 Zylinderschrauben mit Innensechskant  
 M16x min.50, ISO 4762 8.8  
 Anzugsmoment je Schraube 210 Nm

ECE-Genemigung:

**(E1)** R55 - 01 2637

Admiss. supporting load: > 25 km/h= 1000 kg  
 < 25 km/h= 2000 kg  
 Zul. statische Stützlast: > 25 km/h= 1000 kg  
 < 25 km/h= 2000 kg

Connection with Bolt couplings: Bolt coupling to the guideline  
 ECE-55-01 or suitable for recording of drawbar eyes  
 according to DIN 74054 or indentical.

Verbindung mit Bolzenkupplungen: Anhängerkupplungen gemäß Richtlinie ECE-55-01  
 sowie Anhängerkupplungen, die zur Aufnahme von  
 Zugösen DIN 74054 oder baugleichen geeignet sind.

max. D-Value: 125 kN  
 max. D-Wert: 125 kN

max. Dc-Value: 100 kN  
 max. Dc-Wert: 100 kN

max V-Value: 40 kN  
 max V-Wert: 40 kN



**VBG GROUP**

Description  
 Drawbar eye compl.

Modified Date	Modified by	Modification No.	Issue
17.09.2014	RB	12419	
3D Model No.			Engineer
10990548			
Sheet Size	Scale	Projection	Drafting Date
A3	1 : 4		17.09.2014
Stage	Drawing No.	Drafted by	
	10990548-info	RB	

This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.